

Código Comercial	Potência (W)	Bulbo	Tensão (V)	Base	Acabamento	Fluxo luminoso (lm)	Eficiência luminosa (lm/W)	Vida mediana (horas)*	Dimensões em mm	
									Ø	Altura
Standard										
STD-127V25-N	25	A55	127	E27	CLARA	230	9	750	55,0	97,0
STD-220V25-N	25	A55	220	E27	CLARA	220	9	1.000	55,0	97,0
STD-127V40-N	40	A55	127	E27	CLARA	516	13	750	55,0	97,0
STD-220V40-N	40	A55	220	E27	CLARA	415	10	1.000	55,0	97,0
STD-127V60-N	60	A55	127	E27	CLARA	864	14	750	55,0	97,0
STD-220V60-N	60	A55	220	E27	CLARA	715	12	1.000	55,0	97,0
STD-127V100-N	100	A55	127	E27	CLARA	1.620	16	750	55,0	97,0
STD-220V100-N	100	A55	220	E27	CLARA	1.350	14	1.000	55,0	97,0
STD-127V150	150	A65	127	E27	CLARA	2.505	17	750	65,0	125,0
STD-220V150	150	A65	220	E27	CLARA	2.180	14	1.000	65,0	125,0
STD-127V200	200	A65	127	E27	CLARA	3.520	18	750	65,0	125,0
STD-220V200	200	A65	220	E27	CLARA	3.090	15	1.000	65,0	125,0



Código Comercial	Potência (W)	Bulbo	Tensão (V)	Base	Acabamento	Fluxo luminoso	Eficiência luminosa	Vida mediana	Dimensões em mm	
						(lm)	(lm/W)	(horas)*	Ø	Altura
Soft										
SOFT-127V25	25	E60	127	E27	SUAVE	230	9	1.000	60,0	106,0
SOFT-220V25	25	E60	220	E27	SUAVE	230	9	1.000	60,0	106,0
SOFT-127V40	40	E60	127	E27	SUAVE	516	13	1.000	60,0	106,0
SOFT-220V40	40	E60	220	E27	SUAVE	415	10	1.000	60,0	106,0
SOFT-127V60	60	E60	127	E27	SUAVE	864	14	1.000	60,0	106,0
SOFT-220V60	60	E60	220	E27	SUAVE	715	12	1.000	60,0	106,0
SOFT-127V100	100	E60	127	E27	SUAVE	1.620	16	1.000	60,0	106,0
SOFT-220V100	100	E60	220	E27	SUAVE	1.350	14	1.000	60,0	106,0



Código Comercial	Potência (W)	Bulbo	Tensão (V)	Base	Acabamento	Fluxo luminoso	Eficiência luminosa	Vida mediana	Dimensões em mm	
						(lm)	(lm/W)	(horas)*	Ø	Altura
Vela Balão										
VB-CL-127V60-BR	60	BF50	127	E27	CLARA	750	12	1.000	54,0	127,5
VB-CL-220V60-BR	60	BF50	220	E27	CLARA	730	12	1.000	54,0	127,5
VB-AG-127V60-BR	60	BF50	127	E27	SUAVE	740	12	1.000	54,0	127,5
VB-AG-220V60-BR	60	BF50	220	E27	SUAVE	680	11	1.000	54,0	127,5



Código Comercial	Potência (W)	Bulbo	Tensão (V)	Base	Acabamento	Fluxo luminoso	Eficiência luminosa	Vida mediana	Dimensões em mm	
						(lm)	(lm/W)	(horas)*	Ø	Altura
Vela Lisa										
VL-CL-127V25-BR	25	B35	127	E27	CLARA	255	10	1.000	35,0	96,0
VL-CL-220V25-BR	25	B35	220	E27	CLARA	205	8	1.000	35,0	96,0
VL-CL-127V40-BR	40	B35	127	E27	CLARA	480	12	1.000	35,0	96,0
VL-CL-220V40-BR	40	B35	220	E27	CLARA	395	10	1.000	35,0	96,0
VL-AG-127V25-BR	25	B35	127	E27	SUAVE	255	10	1.000	35,0	96,0
VL-AG-220V25-BR	25	B35	220	E27	SUAVE	205	8	1.000	35,0	96,0
VL-AG-127V40-BR	40	B35	127	E27	SUAVE	480	12	1.000	35,0	96,0
VL-AG-220V40-BR	40	B35	220	E27	SUAVE	395	10	1.000	35,0	96,0





PORTFÓLIO COMPLETO PARA PROJETOS **ELÉTRICOS** DE ALTO NÍVEL



☎ 55 112894-6470

📞 55 1199404-5515

🌐 www.brasdistribuidora.com.br

📍 Rua Horácio Vergueiro Rudge,
239 anexo 259 - São Paulo-SP

📱 📷 ✕ 📘
@brasdistribuidora